## Some Considerations Related to the New Realization of SAD-69 in Brazil

<u>Leonardo Castro de Oliveira</u> (leonardo@aquarius.ime.eb.br) Instituto Militar de Engenharia - IME / Departamento de Engenharia Cartográfica Praça General Tibúrcio, 80 - Praia Vermelha - Rio de Janeiro RJ Brazil 22270-290

João Fransisco Galera Monico (galera@stetnet.com.br)
Universidade Estadual Paulista - UNESP / Departamento de Cartografia
Rua Roberto Simonsen, 305 Presidente Prudente São Paulo Brazil 19060-900

Marcelo Carvalho dos Santos (mcsantos@geoc.ufpr.br)
Universidade Federal do Paraná / Departamento de Geociências
CP 19011 - Jardim das Américas - Curitiba Paraná Brazil 81531-970

Denizar Blitzkow (dblitzko@usp.br)
Universidade de São Paulo / Departamento de Engenharia Transportes
Av. Prof. Almeida Prado, s/n - Cidade Universitária - São Paulo SP Brazil 05508-900

## ABSTRACT

IBGE - the institution responsible for the Brazilian Geodetic System (SGB) has been working for more than 10 years in order to readjust the observables belonging to this system. This work was finished at the end of 1996, but the results have not been made available to the public yet. The two main reasons are: 1) the realization of the SIRGAS project is almost finished; 2) there is still a need for complementary analysis of the results. In this presentation, a few aspects related to the new realization of the SAD-69 in Brazil will be shown, taking into account its accuracy and the aspects related to the conversion between the new and the old realizations. For the last case, it was carried out by using either the seven or three parameters model. Taking into account the applications related to Geodesy and Cartography, the results may not be satisfactory. The average results showed an agreement of the order of 2.21 meters for seven, and the 3.69 meters for three parameters respectively. Further investigations should be carried out. The analysis of the accuracy was based on 34 GPS stations, which are coincidents with the conventional network, and their coordinates were considered as true values. A total of 34 adjustments was carried out, in such way that the GPS derived observables of one station were neglected. The estimated coordinates were compared with the true ones. The results, although very limited, shown an improvement of the new realization. For a more conclusive analysis, further GPS stations would be required. The analysis of the several tests will be shown in this presentation.